

LANA GATTO

SUPER SOFT

TRAPEZE PULL

LANA GATTO

Size: 12 (16)

NOTE: figures in brackets () refer to larger size. Where only one figure is given this refers to both sizes.

Skill Level: intermediate

How much yarn:

g 700 (800) of Super Soft yarn, in burgundy shade n. 10105

Needles: Pair of 3.00 mm (no. 11) knitting needles

Pair of 4.00 mm (no. 8) knitting needles

Sewing needle: Yarn needle with rounded point

STITCHES

Tubular stitch - Stocking stitch (st st) - K2, P2 rib.

CHECK PATTERN: (work over a multiple of 4 sts)

Row 1(RS): * K2, P2; rep from * to end. **Row 2:** * K2, P2; rep from * to end. **Row 3:** * P2, K2; rep from * to end. **Row 4:** * P2, K2; rep from * to end. Rep Rows 1-4 throughout.

HOLED FAKE CABLES: (work over a multiple of 6 sts)

Row 1(RS): K to end. **Row 2:** P to end. **Row 3:** K6, turn, P6, turn, work 6 rows in st st only on these 6 sts, leaving rem sts unworked.; * K9, turn, P6, turn leaving first sts unworked and work 6 rows in st st only on these 6 sts, leaving rem sts unworked; rep from * to end (until last 6 sts are worked). **Row 4:** after last P6 on previous row, continue to work P all sts before unworked. Rep these 4 rows once.

TENSIONS

26 sts and 30 rows measure 10 cm square over check patt with 4.00 mm (no. 8) needles.

INSTRUCTIONS

Back: with 3.00 mm (no. 11) needles cast on 110 (122) sts. Work 4 rows in tubular st and continue to work in K2, P2 rib, starting and ending with K2 (on RS) until Border measures 15 (16) cm from beg. Change to 4.00 mm (no. 8) needles. Cont as follows: work in st st first and last 3 sts and, at the same time, work in check patt centre 104 (116) sts. Create wing sleeves as follows: * inside first and last 3 sts in st st, inc 1 st every row 6 times, then work 2 rows straight; rep from * 7 (8) more times. There are 206 (230) sts. Then work 36 (42) more rows straight. ** Shape sleeves and shoulders as follows: cast off 2 sts at beg of next 6 (10) rows, (cast off 3 sts at beg of next 2 rows, cast off 2 sts at beg of foll 2 rows) 13 times, then cast off 2 (3) sts at beg of next 4 (6) rows. Cast off for neck edge rem 56 (62) sts.

Front: work as Back to **. Shape sleeves and shoulders as follows: cast off 2 sts at beg of next 6 (10) rows, (cast off 3 sts at beg of next 2 rows, cast off 2 sts at beg of foll 2 rows) 8 times: 114 (130) sts remain. Shape neck: **Next row:** patt 48 (54) sts, cast off centre 20 (22) sts, patt to end. Join another ball of same yarn and cont separately at the same

time on each side. On neck edge of both sides cast off 2 sts on next and every alternate row 7 (8) times and every foll 4th row twice. At the same time, on shoulder edge of both sides cont as made for Back: (cast off 3 sts at beg of next 2 rows, cast off 2 sts at beg of foll 2 rows) 5 times, then cast off 2 (3) sts at beg of next 4 (6) rows. No sts remain.

Collar: with 4.00 mm (no. 8) needles cast on 126 (138) sts. Work up down. For border work 8 rows in holed fake cables and 2 rows in st st. Cont as follows: work first and last 3 sts in st st and centre 120 (132) sts in check patt. When Collar measures 32 cm from border, work 4 rows in st st. Cast off loosely.

Shoulder-and-sleeve borders: with 4.00 mm (no. 8) needles cast on 90 (96) sts. Work 8 rows in holed fake cables and 2 rows in st st. Cast off all sts.

Sleeves cuffs: with 3.00 mm (no. 11) needles cast on 94 (102) sts. Work 4 rows in tubular st and continue to work in K2, P2 rib, starting and ending with K2 (on RS) until Cuff measures 5 cm from beg. Cast off.

FINISHING

With yarn needle sew a long side of a shoulder-and-sleeve border to cast-off sts to left side of Front, then sew the other long side of same shoulder-and-sleeve border to cast-off sts to corresponding side of Back. Sew other shoulder-and-sleeve border to cast-off sts to right side of Front, then sew the other long side of same shoulder-and-sleeve border to cast-off sts to corresponding side of Back. Sew Front and Back side seams. Join side seams of cuffs in mattress st to form a ring, then sew cast-off sts of each sleeve cuff to sleeve side, in position. Join side seams of collar in mattress st to form a ring: place this seam at centre of back neck-edge; then, with WS of collar facing, join cast-off sts of collar around neck-edge. Fold in half holed fake cable border and sew in position. At end turn half collar outside on RS of work.

