



## General Information

The quantities of yarn are based on average requirements and are therefore approximate. It is essential to work to the stated tension and you should always knit a tension square before starting. If you have too many stitches to 10cm/4in your tension is tight and you should change to a larger needle. If there are too few stitches, your tension is loose and you should change to a smaller needle.

We cannot accept responsibility for the finished product if any yarn other than the one specified is used.

Instructions given are for the first size, with larger sizes in round brackets. Where only one size is given this applies to all sizes. Work all directions in square brackets the number of times stated.

When working with random dyed yarn, to avoid a sudden jump in colour when starting a new ball, start at a similar place in the colour shading.

See ball band for washing and pressing instructions.

### Standard Abbreviations

- alt** = alternate
- beg** = beginning
- cont** = continue
- dec** = decrease
- fol** = following
- gst** = garter stitch
- inc** = increase
- k** = knit
- m1** = make one by picking up the loop lying between st just worked and next st and working into back of it
- patt** = pattern
- p** = purl
- pssso** = pass slipped st over
- rem** = remaining
- rep** = repeat
- skpo** = slip 1, knit 1, pass slipped stitch over
- sl** = slip
- st(s)** = stitch(es)
- st st** = stocking stitch
- tbl** = through back loop
- tog** = together
- yf** = yarn forward
- yon** = yarn over needle
- yrn** = yarn round needle

### USA Glossary

- Cast off** = bind off
- Moss Stitch** = seed stitch
- Tension** = gauge
- Stocking stitch** = stockinette stitch
- Yarn forward, yarn over needle, or yarn round needle** = yarn over

# Knot Cable Jacket

## MEASUREMENTS

|                     |                |                |                  |          |
|---------------------|----------------|----------------|------------------|----------|
| To fit bust         | 81-86<br>32-34 | 91-97<br>36-38 | 102-107<br>40-42 | cm<br>in |
| Actual measurements |                |                |                  |          |
| Bust                | 102<br>40½     | 109<br>43      | 116<br>45½       | cm<br>in |
| Length to shoulder  | 53<br>20¾      | 60<br>23¾      | 60<br>23¾        | cm<br>in |
| Sleeve seam         | 46<br>18       | 46<br>18       | 46<br>18         | cm<br>in |

## MATERIALS

550(600:650)g of Noro Silk Garden in shade 74.

Pair each of 4mm(US 6) and 5mm(US 8) knitting needles.

Cable needle.

56cm/22in open ended zip.

## TENSIONS

27.5 sts and 22 rows to 10cm/4in square over cable panel patt using 5mm(US 8) needles.

22 sts and 24 rows to 10cm/4in square over cable and twist sleeve patt using 5mm(US 8) needles.

## ABBREVIATIONS

**C4B** = slip next 2 sts on to cable needle, hold at back, k2, k2 from cable needle.

**C4BP** = slip next 2 sts on to cable needle, hold at back, k2, p2 from cable needle.

**C4F** = slip next 2 sts on to cable needle, hold at front, k2, k2 from cable needle.

**C4FP** = slip next 2 sts on to cable needle, hold at front, p2, k2 from cable needle.

**T2L** = k into back of 2nd st, then into front of 1st st, slip both sts off needle together.

**T2R** = k into front of 2nd st, then into back of 1st st, slip both sts off needle tog.

Also see page 6.

## KNOT CABLE PANEL A

Worked over 22 sts.

**1st row** P1, C4BP, C4FP, C4B, C4BP, C4FP, p1.

**2nd and every wrong side row** K and p the sts as they appear.

**3rd row** P1, k2, p4, [C4F] twice, p4, k2, p1.

**5th row** P1, k2, p4, k2, C4B, k2, p4, k2, p1.

**7th row** As 3rd row.

**9th row** P1, C4FP, C4BP, C4B, C4FP, C4BP, p1.

**11th row** P3, C4B, p2, k4, p2, C4B, p3.

**13th row** P3, k4, p2, C4B, p2, k4, p3.

**15th row** As 11th row.

**16th row** As 2nd row.

These 16 rows form the patt.

## KNOT CABLE PANEL B

Worked over 22 sts.

**1st row** P1, C4BP, C4FP, C4B, C4BP, C4FP, p1.

**2nd and every wrong side row** K and p the sts as they appear.

**3rd row** P1, k2, p4, [C4B] twice, p4, k2, p1.

**5th row** P1, k2, p4, k2, C4F, k2, p4, k2, p1.

**7th row** As 3rd row.

**9th row** P1, C4FP, C4BP, C4F, C4FP, C4BP, p1.

**11th row** P3, C4F, p2, k4, p2, C4F, p3.

**13th row** P3, k4, p2, C4F, p2, k4, p3.

**15th row** As 11th row.

**16th row** As 2nd row.

These 16 rows form the patt.

## BACK

With 4mm(US 6) needles, cast on 118(126:134) sts.

**1st row** (right side) [P2, T2R] 1(2:3) times, p2, k4, \* p2, T2R, [p2, k4] 3 times \*, rep from \* to \* once, p2, T2R, p2, T2L, p2, \*\* [k4, p2] 3 times, T2L, p2 \*\*, rep from \*\* to \*\* once, k4, p2, [T2L, p2] 1(2:3) times.

**2nd and every wrong side row** K and p the sts as they appear.

These 2 rows form twists between cable panels.

**3rd row** Patt 6(10:14), C4B, [patt 6, C4B, p2, k4, p2, C4B] twice, patt 10, [C4F, p2, k4, p2, C4F, patt 6] twice, C4F, patt 6(10:14).

**5th row** Patt 6(10:14), k4, [patt 6, k4, p2, C4B, p2, k4] twice, patt 10, [k4, p2, C4F, p2, k4, patt 6] twice, k4, patt 6(10:14).  
2nd to 5th rows form the welt patt.  
Work 10 more rows, so ending with a 3rd row.

**Set up row** (wrong side) Patt 0(4:8), [patt 16, m1] twice, patt 6, m1, patt 16, m1, patt 10, m1, patt 16, m1, patt 6, [m1, patt 16] twice, patt 0(4:8). 126(134:142) sts.  
Change to 5mm(US 8) needles.

**1st row** Patt 14(18:22), [work 22 sts of 1st row of cable panel A, T2R] twice, p2, [T2L, work 22 sts of 1st row of cable panel B] twice, patt 14(18:22).

This row sets the position of the cable panels with twists between and the rope cable and twist at each side.

Cont in patt for 15 more rows

**Inc row** (right side) K1, m1, patt to last st, m1, k1.

Taking next 3 incs into rope cable and foll 2 incs into reverse st st, inc in this way at each end of 5 foll 4th rows. 138(146:154) sts.

Patt until back measures  
33(38:36)cm/13(15:14¼)in from cast on edge, ending with a wrong side row.

#### Shape armholes

Cast off 6 sts at beg of next 2 rows.  
Dec one st at each end of next 11 rows.  
104(112:120) sts.

Patt until back measures  
53(60:60)cm/20¾(23½:23¼)in from cast on edge, ending with a wrong side row.  
Cast off.

#### LEFT FRONT

With 4mm(US 6) needles, cast on 60(64:68) sts.

**1st row** (right side) [P2, T2R] 1(2:3) times, p2, k4, \* p2, T2R, [p2, k4] 3 times \*, rep from \* to \*, p2, T2R, k2.

**2nd and every wrong side row** K2, k and p the sts as they appear to end.

These 2 rows form twists between cable panels with k2 at front edge on every row.

**3rd row** Patt 6(10:14), C4B, [patt 6, C4B, p2, k4, p2, C4B] twice, patt 4, k2.

**5th row** Patt 6(10:14), k4, [patt 6, k4, p2, C4B, p2, k4] twice, patt 4, k2.

2nd to 5th rows form the welt patt.

Work 10 more rows, so ending with a 3rd row.

**Set up row** (wrong side) Patt 6, [m1, patt 16,

m1, patt 6] twice, patt 10(14:18). 64(68:72) sts.

Change to 5mm(US 8) needles.

**1st row** Patt 14(18:22), [work 22 sts of 1st row of cable panel A, T2R] twice, k2.

This row sets the position of the cable panels with twists between and the rope cable and twist at side, with 2 garter sts at front edge.

Cont in patt for 15 more rows

**Inc row** (right side) K1, m1, patt to end  
Taking next 3 incs into rope cable and foll 2 incs into reverse st st, inc in this way at beg of 5 foll 4th rows. 70(74:78) sts.

Patt until front measures  
33(38:36)cm/13(15:14¼)in from cast on edge, ending with a wrong side row.

#### Shape armhole

Cast off 6 sts at beg of next row.

Patt 1 row.

Dec one st at armhole edge on next 11 rows.  
53(57:61) sts.

Patt until 10th row of next cable panel has been completed.

#### Shape neck

**Next row** (right side) Patt 35(39:43), turn and leave 18 sts on a holder for collar.

Dec one st at neck edge on next 7 rows.  
28(32:36) sts.

Patt until front is 2 rows longer than Back.  
Cast off.

#### RIGHT FRONT

With 4mm(US 6) needles, cast on 60(64:68) sts.

**1st row** (right side) K2, T2L, p2, \*\* [k4, p2] 3 times, T2L, p2 \*\*, rep from \*\* to \*\*, k4, p2, [T2L, p2] 1(2:3) times.

**2nd and every wrong side row** K and p the sts as they appear to last 2 sts, k2.

These 2 rows form twists between cable panels with k2 at front edge on every row.

**3rd row** K2, patt 4, [C4F, p2, k4, p2, C4F, patt 6] twice, C4F, patt 6(10:14).

**5th row** K2, patt 4, [k4, p2, C4F, p2, k4, patt 6] twice, k4, patt 6(10:14).

2nd to 5th rows form the patt.

Work 10 more rows, so ending with a 3rd row.

**Set up row** (wrong side) Patt 0(4:8), [patt 16, m1] twice, patt 6, m1, patt 16, m1, patt 6. 64(68:72) sts.

Change to 5mm(US 8) needles.

**1st row** Patt 6, [work 22 sts of 1st row of cable panel B, T2L] twice, patt 12(16:20).

This row sets the position of the cable panels with twists between and rope cable and twist at each side.

Cont in patt for 15 more rows.

**Inc row** (right side) Patt to last st, m1, k1.

Taking next 3 incs into rope cable and foll 2 incs into reverse st st, inc in this way at end of 5 foll 4th rows. 70(74:78) sts.

Patt until front measures

33(38:36)cm/13(15:14½)in from cast on edge, ending with a right side row.

#### Shape armhole

Cast off 6 sts at beg of next row.

Dec one st at armhole edge on next 11 rows. 53(57:61) sts.

Patt until 10th row of next cable panel has been completed.

#### Shape neck

**Next row** (right side) K2, leaving a long end, break yarn, slip these 2 sts and next 16 sts onto a holder for collar, rejoin yarn to rem sts, patt to end. 35(39:43) sts.

Dec one st at neck edge on next 7 rows. 28(32:36) sts.

Patt until front is 2 rows longer than Back. Cast off.

#### LEFT SLEEVE

With 4mm(US 6) needles, cast on 46(46:56) sts.

**1st row** (right side) P2, T2L, p2, [k4, p2, T2L, p2] to end.

**2nd row** K and p the sts as they appear.

**3rd row** P2, T2L, p2, [C4B, p2, T2L, p2, C4F, p2, T2L, p2] twice, [C4B, p2, T2L, p2] 0(0:1) time.

**4th row** As 2nd row.

These 4 rows form the rope cable and twist patt.

Work 6 more rows.

Change to 5mm(US 8) needles.

Inc and take into rope cable and twist patt, one st at each end of next row, then on 9(1:3) foll 6th rows, then every foll 4th row until there are 86(94:102) sts.

Work straight in patt until sleeve measures 46cm/18in from cast on edge, ending with a wrong side row.

#### Shape top

Cast off 6 sts at beg of next 2 rows.

Dec one st at each end of next 11 right side rows. 52(60:68) sts.

Dec one st at each end of next 11 rows. 30(38:46) sts.

Cast off.

#### RIGHT SLEEVE

Work as given for Left Sleeve but working T2R for T2L.

#### COLLAR

Matching cable sts, join shoulders. With right side facing and 4mm(US 6) needles, slip 2, patt 16 from right front holder, pick up and k13 sts up right front neck, 46 sts across back neck and 13 sts down left front neck, patt 18 sts from holder. 108 sts.

**Set up row** (wrong side) K2, p2, k2tog, k1, \* [p4, k2] 4 times, p2, [k2, p4] twice, [k2, p2] 4 times, k2, [p4, k2] twice, p2, [k2, p4] 4 times \*, k1, skpo, p2, k2. 106 sts.

**1st row** K2, T2L, p2, [C4F, p2] 4 times, T2L, [p2, C4F] twice, [p2, T2R] twice, p2, [T2L, p2] twice, [C4B, p2] twice, T2R, [p2, C4B] 4 times, p2, T2R, k2.

**2nd row** K2, p2, k2, work as set up row from \* to \*, k2, p2, k2.

**3rd row** K2, T2L, [k4, p2] 4 times, T2L, [p2, k4] twice, [p2, T2R] twice, p2, [T2L, p2] twice, [k4, p2] twice, T2R, [p2, k4] 4 times, p2, T2R, k2.

**4th row** As 2nd row.

These 4 rows form the collar patt.

Work until collar measures 14cm/5½in, ending with a wrong side row.

Cast off.

#### TO MAKE UP

Mark centre of front edges of collar. Pin and tack zip in place ending at markers. Trim zip at top edges if necessary and secure ends. Using matching sewing thread, sew in zip. Fold collar in half to wrong side. Sew row ends of collar to wrong side of zip and slip stitch cast off edge to pick up row. Sew sleeves into armholes. Join side and sleeve seams.